



SELECT DOOR
artistry and attention to detail

Installation Information

Failure to follow these instructions may void the product warranty

A. Upon Delivery

1. INSPECT each unit for defects or damage.
2. STORE flat, on a level surface, or on edge with support, in a dry, well ventilated building out of direct sunlight and never in contact with a cement floor. Prehung units may be stored standing, providing doors are supported by cleats and stops. Cover with drop cloth to keep clean, but do not stop air circulation.
3. DO NOT SUBJECT to abnormal heat, dryness, humidity or sudden changes of conditions. Relative humidity should not be less than 25% nor greater than 55%
4. Some species are sensitive to light. Cover with drop cloth to keep wood from changing shades.
5. Store doors in closed in building with an operational HVAC system for ideal conditions.
6. Paint or finish as soon as possible.

Interior:

Paint Grade, within 3 months. Stain Grade, within one month

Exterior:

Paint Grade, within 3 months. Stain Grade immediately upon installation.

B. Installation

1. Install products as soon as they have acclimated to the average humidity of the locality. Prehung units must be installed plumb and square.
Note: Jamb legs on interior units are longer than the door. Trim legs as necessary for desired floor clearance.
2. Structural integrity must not be impaired by fitting or by the installation of hardware.
3. DO NOT COVER UNIT OR DOORS WITH PLASTIC SHEETING. Plastic may hold moisture and/ or create an extreme temperature build-up which can affect the integrity of the products and its finish. If protection of the product is required during construction, we recommend covering with plywood or other wood-base building sheathing to allow air circulation.
4. STORM DOORS – SELECT does not recommend the use of storm doors where direct sunlight through the storm door will create extreme temperatures. Such extremes may affect the integrity of the door and its finish. If storm doors are necessary to protect against extreme weather conditions, the glass must have a sun screen or be tinted to minimize the effects of direct sunlight. Ventilation to reduce heat build up is also necessary.



SELECT DOOR
artistry and attention to detail

Installation Information

(continued)

5. If the finish is altered for installation, fitting or weatherstripping, the work must be re-sealed (stained, sealed and top coated) immediately.
6. Adequate overhangs must be provided to protect the product from the elements. Adequate overhang depends on the normal weather conditions of the area where the product is to be used. Typically an adequate overhang would be a distance extending to one half the elevation of the entire unit.
7. When the product is exposed to rain or excessive moisture, sealing around the moldings, glass and panels with a high-quality paintable caulking is required after finishing is complete.